Eaton S500-5-R

Catalog Number: S500-5-R

Eaton S500 Series Fast-acting fuse 5A, 250 Vac or less, 32 Vdc (self certified), S500-5-R



General specifications

Product Name	Catalog Number
Eaton Bussmann series S500 fast-acting S500-5-R	
fuse	UPC
	051712643641
Product Length/Depth	Product Height
20.5 mm	5.2 mm
Product Width	Product Weight
5.2 mm	0.67 g
Warranty	Compliances
Not Applicable	RoHS Compliant
	CCC Marked
	CE Marked

Certifications VDE



Product specifications

Туре

Electronic

Application

Electronic circuits

Amperage Rating

5 A

Frequency rating - max 50 Hz

Frequency rating - min 50 Hz

Voltage drop 120 mV maximum

Interrupt rating

50 AIC at 250 Vac

Fuse indicator

Non-indicating

Connection Ferrule end x ferrule end

Material

Glass tube Nickel-plated end-cap construction

Quantity

100

Voltage rating 250 Vac or less, 32 Vdc (self certified)



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia

Resources

Specifications and datasheets

Eaton S500 glass tube fuses data sheet

Eaton Specification Sheet - S500-5-R